

Product Code: CMA147PL

## **Technical Specification**



Description: 2 Gang Unfurnished Dimmer Plate & Knobs (1200W Max) - 3 Apertures





## **General Information**

**Plate Dimensions (mm)** 146 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Rounded Profile Colour Polar White

Materials Front Plate & Control Button: Urea

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Terminals: Brass

Anti Microbial Certified Yes

Termination Type Screw Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 25

Standards BS 5733

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

## Compatible Dimmer Modules

MD9014: 100W Dual Mode LED Dimmer Module

MDg001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module

MD9010: 1-10V Analogue Rotary Dimmer Module

Specification is subject to change without notice. Errors & Omissions excluded.

E: sales@scolmore.com | W: scolmore.com



Page 1 of 1 (02-01-2024)







