

Product Code: CMA502

Technical Specification



Description: 45A 2 Gang (Vertical) Double Pole Plate Switch With White Rocker







General Information

Plate Dimensions (mm) 86 (W) x 146 (H) x 9.5 (D)

Plate Fixing Centres - Vertical (mm) 120.6

> Style Rounded Profile Colour Polar White Materials Front Plate: Urea

> > Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Rear Housing: Urea

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Anti Microbial Certified

Operating Voltage (AC) Frequency (Hz) 50 250

Resistive Load Rating (A) Termination Type Screw

Terminal Size (mm)

Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 1 x 16 Double Pole Switch Yes

Twin Earth Terminals Yes Product Marking On & Off

Minimum Back Box Depth (mm)

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom









