

Product Code: CMA623

Technical Specification

Luckinslive 389783129





Description: 20A Double Pole Plate Switch With Neon



General Information

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Colour Polar White

Materials Front Plate & Rocker Switch: Urea

Neon Lens: Polycarbonate Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Rear Housing: Urea

Contacts: Silver "on-lay" Copper / Brass

Anti Microbial Certified

Operating Voltage (AC) Frequency (Hz) 50 250

Resistive Load Rating (A) Termination Type Screw

> Terminal Torque Value (Nm) 1.8 Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 Double Pole Switch Yes

Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Orange

Minimum Back Box Depth (mm)

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.









