essentials™

Technical Specification

Product Code: CL011B Luckinslive 389086321

Description: 10AX 1 Gang 2 Way Plate Switch (No Knockouts)





General Information

 $\textbf{Dimensions (mm)} \quad 80 \ (\text{W}) \times 80 \ (\text{H}) \times 42 \ (\text{D})$

Plate Fixing Centres - Horizontal (mm) 60.3

MiniGrid Plate (Gang) 1

MiniGrid Single Width Module Quantity

MiniGrid Double Width Module Quantity

Style Metal Clad

Colour Grey
Insert Colour White

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Rear Housing: Nylon

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Operating Voltage (AC) 25 Inductive Load Rating (AX) 10

ductive Load Rating (AA) 10

Load Rating Comments Suitable for Fluorescent or Inductive Loads

Termination Type Screw

Terminal Size (mm) Ø3.5

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

Modular Rocker Switches Yes

2 Way Switch Yes

Supplied Back Box Depth (mm) 40
Back Box Knockouts - Total (mm) None
Back Box Earth Terminal Supplied Yes

Ingress Protection IP20

Operational Temperature (°C) -5 to +40 Warranty (Years) 20

, , , , , , , , , , , , , , , , , , ,

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)







MINIGRID®

Insert & Rocker Switch: Urea

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 0.5

Earth Strap: Mild Steel





Specification is subject to change without notice. Errors & Omissions excluded.