

Product Code: CL1836

Luckinslive 436091052

Description: 13A 2 Gang Double Pole Safety Shutter Switched Socket Outlet With Outboard Rockers



**General Information**

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Metal Clad		
Colour	Grey		
Materials	Front Plate & Mounting Box:	Electrophoretically Coated Steel	
	Rear Housing:	Urea	
	Terminal Screws:	Steel & Yellow Passivated	
	Internal Busbars:	Formed Pressed Brass	
Operating Voltage (AC)	250	Insert & Rocker Switch:	Urea
Resistive Load Rating (A)	13	Terminals:	Brass
Termination Type	Screw	Contacts:	Silver "on-lay" Copper / Brass
Terminal Size (mm)	Ø5	Earth Strap:	Mild Steel
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4	Frequency (Hz)	50
Double Pole Switch	Yes	Terminal Torque Value (Nm)	2
3 Pin Safety Shuttered	Yes		
Twin Earth Terminals	Yes		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	7 x Ø20	Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Rear (mm)	None
Back Box Knockouts - Bottom (mm)	2 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

**Standards** BS 1363-2

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

The safety shutter will only fully open when all three BS 1363 plug-top pins engage correctly with the shutter. Inserting the earth pin alone will not open the live and neutral shutter like conventional socket shutters.

