



Product Code: CL201

Luckinslive 389086596

Description: 45A 1 Gang Double Pole Plate Switch With Neon



General Information

| | | | |
|--|---|--|---------|
| Dimensions (mm) | 80 (W) x 80 (H) x 52 (D) | | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | | |
| Style | Metal Clad | | |
| Colour | Grey | | |
| Materials | Front Plate & Mounting Box: Electrophoretically Coated Steel Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass | Insert, Switch & Rear Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 45 | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø6 | Terminal Torque Value (Nm) | 2.5 |
| Terminal Capacity - Solid (mm²) | 1 x 16 | | |
| Double Pole Switch | Yes | | |
| Twin Earth Terminals | Yes | | |
| | | Indicator Colour | Red |
| Product Marking | On & Off | | |
| Supplied Back Box Depth (mm) | 50 | | |
| Back Box Knockouts - Total (mm) | 5 x Ø20 | Back Box Knockouts - Sides (mm) | 1 x Ø20 |
| Back Box Knockouts - Top (mm) | 2 x Ø20 | Back Box Knockouts - Rear (mm) | None |
| Back Box Knockouts - Bottom (mm) | 1 x Ø20 | | |
| Back Box Earth Terminal Supplied | Yes | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

