

Product Code: CT1400

Description: 20A 4 Pole Flow™ Ceiling Rose (Without Cover)



General Information

Dimensions (mm)	85 (Dia) x 35	
Insert Colour	Blue	
Materials	Cover: Polycarbonate	Base & Terminal Housing: Nylon (PA66)
	Terminals: Silver Plated Brass	Terminal Screws: Steel and Yellow Passivated
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Rated Impulse Voltage (kV)	4	
Recommended Inner Core Strip Length (mm)	L & N: 35; E: 43	
Recommended Conductor Strip Length (mm)	10	
Termination Type	Screw	
Terminal Size (mm)	Ø4.2	Terminal Torque Value (Nm) 0.8
Terminal Capacity - Solid (mm ²)	3 x 2.5	
Terminal Capacity - Flex (mm ²)	3 x 1.5	
Termination Layout (Female)	L - E - N - A	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 8488, BS EN 61535, BS 5733

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.

Connector Information Compatible Connectors (Without CT1401 Cover): All 3 Pole & 4 Pole Male Connectors
 Compatible Connectors (With CT1401 Cover): CT101C, CT102C & CT202C (Male Connectors)
 Conduit Installations: Suitable For Installation On To Conduit (BESA) Boxes