

**Product Code:** CT300

**Description:** 250V~ 20A 4 Pole 1 In 3 Out Hub



### General Information

Dimensions (mm)	82 (W) x 82 (D) x 55 (H)	
Insert Colour	Blue	
Materials	Cover: Polycarbonate	Base & Terminal Housing: Nylon (PA66)
	Terminals: Silver Plated Brass	Terminal Screws: Steel and Yellow Passivated
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Rated Impulse Voltage (kV)	4	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

**Standards** BS 8488, BS EN 61535, BS 5733

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation.

Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.

**Compatible Connectors** Input Connector: Compatible With 3 and 4 Pole Connectors (Complete or Female)  
Output Connectors: Compatible with 3 and 4 Pole Male Connectors