

**Product Code:** CT743

**Description:** 6A 4 Pole Connector Pre-wired 0.75mm<sup>2</sup> LSZH To FE - 3M



### General Information

|                               |   |  |
|-------------------------------|---|--|
| CT201M Dimensions (mm)        | 54 (W) x 30 (D) x 22 (H)                                  |  |
| Insert Colour                 | Blue  |  |
| Materials                     | Cover: Polycarbonate                                      | Base & Terminal Housing: Nylon (PA66)        |
|                               | Terminals: Silver Plated Brass                            | Terminal Screws: Steel and Yellow Passivated |
| Operating Voltage (AC)        | 250   | Frequency (Hz) 50                            |
| Resistive Load Rating (A)     | 6   |  |
| Cable - Assembly Rating (A)   | 6   |  |
| Pre-wired Cable Specification | 4G 0.75mm <sup>2</sup> (Low Smoke Zero Halogen) H05Z1Z1-F |  |
| Termination Type              | Screw   |  |
| Cable Restraint Supplied      | Yes   |  |
| Ingress Protection            | IP20  |  |
| Operational Temperature (°C)  | -5 to +40   |  |
| Warranty (Years)              | 10  |  |

**Standards** BS EN 61535, BS 5733, BS EN 50525-3-11

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.