



Product Code: PA303

Luckinslive 38g120012

Description: 13A Resilient Plug Top (5A Fused) Fast Grip



General Information

| | | |
|---------------------------------|--|--------------------------------|
| Dimensions (mm) | 49.5 (W) x 21 (D) x 49.5 (H) | |
| Colour | White | |
| Materials | Body: Nylon | Pins: Brass |
| | Internal Busbars: Formed Pressed Brass | Fuse: BS 1362 Approved |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 5 | |
| Fuse Fitted Type | Plug Top Cartridge Fuse | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø3.1 | Terminal Torque Value (Nm) 0.4 |
| Terminal Capacity - Solid (mm²) | 1.5 | |
| Product Marking | Fused | |
| Cable Entry Dimensions (mm) | Ø10.8 | |
| Cable Restraint Supplied | Yes | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS 1363/A, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Always refer to the circuit diagram supplied with the relevant product.



Catalogue



Range



DoC

