
essentials™

Product Code: PRW213

Technical Specification

Luckinslive 389107572







General Information

Dimensions (mm)

Stvle Colour Polar White

Materials Cover & Pattress: Urea

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A) Termination Type Screw

Twin Screw Terminals

Terminal Size (mm)

Terminal Capacity - Solid (mm²)

Double Pole Switch Twin Earth Terminals No

Neon Indicator Yes

Mechanical Indicator Yes

Mechanical Indicator Type

Supplied Back Box Depth (mm)

Back Box Knockouts - Total (mm)

Back Box Knockouts - Top (mm)

Back Box Knockouts - Bottom (mm) Ingress Protection

Operational Temperature (°C)

Warranty (Years)

100 (Dia) x 77 (D)

Round

Earth Strap: Mild Steel

50

Yes

Ø6.7

1 x 25

Yes

Green Tab

Pattress Supplied

2 x 16 x 8.5 or 23 x 12

None

None

IP20 -5 to +40

25

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom

Specification is subject to change without notice. Errors & Omissions excluded.







Terminal Housing: Urea

Frequency (Hz)

Indicator Colour Orange

Internal Busbars: Formed Pressed Brass

Terminals: Brass

Pull Bell: Urea

Terminal Torque Value (Nm) 2.5

Back Box Knockouts - Sides (mm) 2 x 23 x 12

Back Box Knockouts - Rear (mm) 2 x 16 x 8.5



